


METASU

DE-IONISED WATER



METASU De-Ionised Water contains no solid minerals or other contaminants and does not form scale when exposed to prolonged heat. It thus provides proper heat transfer, long durability and less maintenance of equipment compared to non-treated water.

METASU De-Ionised Water is ideal for the dilution of anti-freeze and screenwash as well as being used to top up batteries and for use in steam irons and other equipment that require the production of steam.

DIRECTIONS

Always consult the equipment manufacturer's handbook.

PACKAGING INFORMATION

ITEM CODE	DESCRIPTION	UNITS PER CASE	UNITS PER LAYER	UNITS PER PALLET
1000	METASU De-ionised Water 1L	12	144	720
1001	METASU De-ionised Water 5L	4	40	160
1002	METASU De-ionised Water 25L	1	16	32

SAFETY

Refer to METASU De-Ionised Water SDS for further information.

TECHNICAL DATA

Refer to METASU De-Ionised Water TDS for further information.

For SDS and TDS please email www.metasuco.com/ or call the number below.

For more information on METASU products visit www.metasu.com

T: +98 (0)21 76509860 | mttaria.co@gmail.com | www.metasuco.com

m.abdollahzadeh co.Roudhen, intersection of Cheshme and University Street, Tehran, Iran.